

Skye Patrol 9000



With a 10° deadrise it is designed to be light and fuel efficient.

Ideal for inland waterways and inshore operations.

Build type: Vacuum infused (Quadriaxial fiberglass cloth 1100G GSM - E glass, Vinylester resin, PVC core) build to DNV class standard.

FEATURE:

- ☑ Centre console with Digital gauge (Tacho and Speedo, Fuel level, Battery level, Trim, Hours)
- ☑ Furuno 4kW radar and chart plotter + GPS
- ☑ VHF DSC / GPS
- ☑ Jockey seats x 8
- ☑ Bow storage locker
- ☑ Console ballistic level 1 protection
- ☑ Max engine 2 x 200 Hp
- ☑ Cradle - shipping and storing
- ☑ Battery x 3
- ☑ Kill Switch - Cord
- ☑ Navigation Light
- ☑ Automatic Bilge Pump
- ☑ Anchor 15kg (including chain and rope)
- ☑ Lifejacket x 8
- ☑ Lifebuoy / Ring
- ☑ 1,5kg DPC Fire Extinguisher

PRINCIPLE DIMENSIONS

| | |
|---------------------------------|----------|
| Length overall | 9.00 m |
| Beam overall | 2.15 m |
| Displacement | 2600 kg |
| Fuel Capacity | 400 L |
| Max Speed | 38 Kts |
| Suzuki 4 stroke outboard engine | 2x200 Hp |